

IN THE CLAIMS

1 (Currently Amended). An organic light emitting display comprising:
a plurality of modules, each including a front plate and a back plate;
~~a front plate having~~ an organic light emitting material formed on one side of said
front plate thereof;
a said back plate secured over said one side of said front plate; and
a filler material including a desiccant mixed into said filler material to seal the
region between said front and back plates; ~~and~~
~~a plurality of modules, each including a front plate and back plate, said filler~~
~~material provided between said modules.~~

Claim 2 (Canceled).

3 (Original). The display of claim 1 wherein said desiccant is a silica.

4 (Original). The display of claim 1 wherein said desiccant is zeolite.

5 (Original). The display of claim 1 wherein said filler material includes epoxy.

Claims 6-10 (Canceled).

11 (Currently Amended). A method comprising:
forming a front plate having an organic light emitting material deposited thereon;
covering said organic light emitting material with a back plate;
sealing the region between said front plate and said back plates with a filler
material including a desiccant mixed into said filler material;
combining a plurality of light emitting device modules to form an array; and
filling the regions between adjacent modules with a filler material including a
desiccant mixed into said filler material.

12 (Original). The method of claim 11 including mixing a filler material into an epoxy.

Claim 13 (Canceled).

14 (Original). The method of claim 11 including mixing zeolite into epoxy to form said filler material.

15 (Original). The method of claim 11 including mixing silica into epoxy to form said filler material.